

Eclipse Plus 250 250 VA

*Uninterruptible Power Supply
with Surge Suppressor*



Advanced Features

- ▶ 250 VA UPS and Surge Suppressor
- ▶ 450 Joule Surge Rating
- ▶ Instantaneous Clamp Time
- ▶ 5-30 Minutes of UPS Back-Up Time
- ▶ 6 Outlets Total, 2 Outlets spaced for Transformer Blocks
- ▶ User-Replaceable Battery
- ▶ Fax/Modem Protection and Connection Cable
- ▶ Cable Organizers and ID Labels Included

MGE, the world leader in Uninterruptible Power Supplies, integrates surge suppression and uninterruptible power supply in one affordable package. Uninterruptible Power Supplies (**UPS**) provide back-up power during power outages for the PC and surge suppression protects peripheral devices if a surge or spike occurs.

MGE's Eclipse Plus 250 is one of the smallest 250 VA UPSs available and also includes a 3-outlet surge suppressor to protect peripherals. And of course, the Eclipse Plus 250 is built to the same quality standards as all MGE UPSs, the quality to last and last.

MGE UPS SYSTEMS is one of the world's largest manufacturers of Power Protection Systems for data centers, networks and PCs with direct presence in over 80 countries worldwide. Other MGE products include: *Power Management Software, Power Conditioners, Surge Suppressors, Ultra-Isolation Transformers, Telecom Inverters and Power Distribution Units.*

THE UNINTERRUPTIBLE POWER PROVIDER

M G E
UPS SYSTEMS

Technical Specifications

UPS Rating: 250 VA/168 W (2.1 A)
 Surge Suppressor Rating: 950 VA (8 A)
 Input Voltage: 120 VAC, 50/60 Hz
 Output Voltage: 120 VAC, 50/60 Hz
 UPS Back-Up Time: 5-30 Minutes
 Surge Suppressor Joule Rating: 450
 Input Plug: NEMA 5-15 straight plug with 4 foot cord
 UPS Output Wave Shape: Modified Sine
 Circuit Breaker: 10 amp
 Operating Temperature: 0-40C up to 1500M
 Storage Temperature: 0-50C
 Battery: 2 Each 12 Volt/4.2 Ah
 Battery Life: 5 Yrs. with Normal Use
 Recharge Time: 8 Hours
 Agency: UL, cUL, FCC
 Warranty: 2 Years Parts & Labor, \$10K Connected Equipment (subject to terms)

Sizing Guide & Back-Up Times

CPU Make	Monitor Size in Inches			
	14	15	16	17
486, Celeron	10 Minutes	7 Minutes		
Pentium, Pentium Pro K 6	10 Minutes	7 Minutes		
Pentium II	5 Minutes	3 Minutes		
Pentium III	5 Minutes	3 Minutes		
iMac		8 Minutes	5 Minutes	
Power Mac G3	5 Minutes	3 Minutes		

Physical Specifications

Size: 10"L x 7"W x 2.6"H
 Weight: 6.6 lbs.
 Accessories: ID labels, Cable Organizers, Fax/Modem Cable
 MGE Part Number: 81003

Back-Up Time Chart

"Computer Outlets"	Back-Up Time
50 VA	30 Minutes
100 VA	21 Minutes
150 VA	10 Minutes
200 VA	7 Minutes
250 VA	5 Minutes

Features

2 normal UPS/surge protected outlets, 1 spaced outlet for transformer block

User-replaceable battery access door on unit bottom

Unit can be wall-mounted with screws (not included)

Red fault indicator

ID labels for protected device identification (not shown)

Cable organizers for neat cable routing (not shown)

Green on utility/on battery indicator



2 surge only protected outlets, 1 spaced outlet for transformer block

6 foot input cord

Output circuit breaker

Fax/modem protector

Contact closures for special applications

On/Off Switch



MGE UPS SYSTEMS

USA (headquarters)
 1660 Scenic Avenue
 Costa Mesa, CA 92626
 tel (800) 523-0142
 (714) 557-1636
 fax (714) 557-9788

CANADA
 #9, 2798 Thamesgate Dr.
 Mississauga, ON L4T 4E8
 tel (905) 672-0990
 (877) 672-0990
 fax (905) 672-7667

ARGENTINA
 Thames 91
 1609 San Isidro
 Prov de Buenos Aires
 tel (54) 11-4766-8777
 fax (54) 11-4766-6008

BRAZIL
 Avenida Cuido
 Caloi 1985 (CALPAO 23)
 Guarapiranga
 Sao Paulo - SP, CEP 05802
 tel (55) 11-5891-2274
 fax (55) 11-5890-3353

MEXICO
 Ave. Congreso de la Union
 #524 Colonia Santa Anita
 Mexico D.F 08300
 tel 525 538 9687
 fax 525 530 7625

www.mgeups.com
 info@mgeups.com

ECS 104
 Effective: January 2003

THE UNINTERRUPTIBLE POWER PROVIDER